

# Melodys Flash


## Outdoor Melodys Flash

## Melodys Flash

### Description:

The Outdoor Melodys Flash emits a luminous signal the same way melodies are broadcasted by the Melodys Sounder (programming is identical to that of the Melodys sounder).

- ▶ Controlled by the Sigma master clock (Sigma P or Sigma Mod) in DHF mode.
- ▶ 1 « Test » push-button (accessible by opening the controller box).
- ▶ 2 LEDs give indications about the operation (LEDs visible by opening the controller box):
  - LED « ~ » (green) indicates that the unit is powered up.
  - LED « Ψ » (green/orange/red) informs about the configuration of the system.
- ▶ Duration of the control signal: 30 seconds.



### Technical characteristics:

- ▶ Orange shockproof polycarbonate lens and black polyamide base.
- ▶ Wall mounting bracket.
- ▶ Power supply: 100 ~ 240VAC (+ 10%) - 50/60Hz.
- ▶ Consumption: 0.5A at 230VAC.
- ▶ Electrical insulation: class I.
- ▶ Power supply connections: 2 terminals - N (neutral) and L (phase) for 2.5mm<sup>2</sup> max. wires.
- ▶ PG11 cable gland for power cable.
- ▶ PG7 cable gland for beacon cable.
- ▶ Distance between the controller and the beacon: 5 meters (the cable is supplied).
- ▶ Protection Index: IP54, IK07.
- ▶ The beacon:
  - Diameter: 105 mm.
  - Weight: 690 gr.
  - Lamp: H1 (70 W).
- ▶ Dimensions control box: L250 x W195 x D97.5 mm.
- ▶ Dimensions of the information sign: 200 x 200 mm , 4mm thick.
- ▶ Operating temperature range: -20 to +50°C.

### Recommendations:

- ▶ We recommend that Outdoor Melodys Flash be installed in direct view of all the people present in the covered area.

### Norms:

- ▶ Directive R&TTE 1999/5/CEE.
- ▶ EN 60950: Safety of the Data processing devices.
- ▶ EN 301-489-3 (CEM of radio product: emission and immunity).
- ▶ EN 300-220-2 (Good use of the radio spectrum).

### Identification of the LEDs and Test button




« Test » button


LED « ~ »

LED « Ψ »

### Dimensions (mm)



### Wall mounting



### Reference Outdoor Melodys Flash

- ▶ Outdoor Melodys Flash – 100 ~ 240VAC

907 597\*

\*The wall mounting bracket is included

